

BLANK PAGE



Indian Standard SPECIFICATION FOR PUDDLER, ANIMAL DRAWN

(Second Reprint FEBRUARY 1996)

UDC 631.314.3

© Copyright 1966

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard SPECIFICATION FOR PUDDLER, ANIMAL DRAWN

Farm Implements and Machinery Sectional Committee, AFDC 20

Chairman

Representing

AGRICULTURAL COMMISSIONER
WITH THE GOVERNMENT OF
INDIA

COMMISSIONER Indian Council of Agricultural Research, New Delhi

Members

AGRICULTURAL ENGINEER

Department of Agriculture, Government of Maharashtra

RESEARCH ENGINEER (Alternate)
SHRI B. C. BAGCHI National Dairy Research Institute, Karnal

SHRI A. K. BANERJEE (Alternate)
BBIG B. S. BAJWA

Directorate of Military Farms, Army Headquarters

SHRI SHAHID ALI (Alternate) SHRI H. V. BHARGAV

Department of Agriculture, Government of Uttar Pradesh

SHRI S. C. BHATNAGAR (Alternate.)

SHRIS. C. DHATNAGAR (Atternate.)

Shbi P. S. Bhatnagar

Directorate General of Technical Development, New Delhi

SHRI M. L. BHATTACHARYYA

Directorate of Industries, Government of West Bengal National Manufacturers and Traders, Kaithal

SHRI DESH RAJ CHOUDHRY

SHEI RAM GOPAL LATEA (Alternate)
RI S. C. GHOSH Ministry of Defence

SHRI S. C. GHOSH SHRI P. L. GOEL

Dandakaranya Project (Ministry of Rehabilitation) Kirloskar Brothers Ltd, Kirloskarvadi

SHRI P. D. GUNE

te)

SHRI D. P. PARKHE (Alternate)
HEAD OF THE AGRICULTURAL

Allahabad Agricultural Institute, Allahabad

ENGINEERING DEPARTMENT
RESEARCH ASSISTANT (Alternate)

DR C. M. JACOB

Punjab Agricultural University, Ludhiana

SHRI S. R. VERMA (Alternate) SHRI S. K. KEMPAIAH

The Mysore Implements Factory, Hassan Directorate of Extension (Ministry of For

SHRI D. N. KHERDEKAR

Directorate of Extension (Ministry of Food & Agriculture)
Voltas Limited, Bombay

SHRI M. K. NANDI

SHRI B. K. S. JAIN (Alternate)

PROF A. C. PANDYA

In personal capacity (Indian Institute of Technology, Kharagpur)

SHRI AMAR NATH PARBHAKAR SHRI RAM PARKASH PARBHA-KAR (Alternate)

The National Engineering Company, Ambala City

(Continued on page 2)

18:3369-1965

(Continued from page 1)

Members

Representing

SHRI L. M. PATEL

American Spring & Pressing Works Private Ltd, Bombay

SHRI SHARAD L. PATEL (Alternate)

COL E. P. RAJU

Development Commissioner, Small Scale Industries (Ministry of Industry & Supply)

SHBI K. N. P. RAO

The Tata Iron and Steel Co Ltd, Jamshedpur

SHRI K. R. VENKATACHALAM
(Alternate)

DR S. E. ROY SHRI H. S. SANDHU Indian Agricultural Research Institute, New Delhi Government Livestock Farm, Hissar

Shbi Satwant Singh

In personal capacity (Nasirpur Farm, Bahadurgarh Fort,
Patiala)

DR M. P. SINHA

Department of Agriculture and Animal Husbandry, Government of Bihar Indian Council of Agricultural Research, New Delhi

SHRI C. S. SRIDHABAN SHRI T. H. NIBMAL (Alternate) SHRI K. S. YADAV

Directorate of Extension (Ministry of Food &

Seri P. H. Ramanathan,
Assistant Director Agri &
Food)

Agriculture)
Director, ISI (Ex-officio Member)

Secretary

SHRI E. N. SUNDAR

Extra Assistant Director (Agri & Food), ISI

Associate Secretary

SHRIS, M. RAZVI

Assistant Director (Mech Eng), ISI

Farm Machinery Subcommittee, AFDC 20:1

Convener

SHRI D. N. KHERDEKAR

Directorate of Extension (Ministry of Food & Agriculture)

Members

SHBI G. R. ATHAVALE SHBI S. L. SAXENA (Alternate) SHBI H. V. BHARGAV National Sugar Institute, Kanpur

DB A. K. DUTT
SHBI GUBCHABAN DASS.
SHBI RAMJI DASS (Alternate)

Department of Agriculture, Government of Uttar Pradesh Dandakaranya Project (Ministry of Rehabilitation) Nahan Foundry Limited, Nahan

SHRI V. C. KAPOOR SHRI R. G. MENON Cossul & Co Private Ltd, Kanpur Indian Institute of Sugarcane Research, Lucknow;

and Indian Central Sugarcane Committee, New Delhi

Kirloskar Brothers Limited, Kirloskarvadi In personal capacity (Indian Institute of Technology,

Shri K. S. Pachapurkar Prof A. C. Pandya

(Continued on page 10)

Kharagbur)

Indian Standard SPECIFICATION FOR PUDDLER, ANIMAL DRAWN

O. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 30 November 1965, after the draft finalized by the Farm Implements and Machinery Sectional Committee had been approved by the Agricultural and Food Products Division Council.
- 0.2 The puddler is an implement specially designed for quick and efficient preparation of paddy fields with standing water after initial ploughing. It breaks up the clods and churns the soil and thereby reduces the number of operations to get the desired tilth.
- 0.3 The puddler may have a number of puddling units (see 2.2) depending upon the size (see 3.1) but most commonly used puddler in the country has only three puddling units. The puddling units each having four paddles (see 2.1 and Fig. 1) are mounted on an axlc. The axle with the puddling units is freely mounted on two bearings fitted on a sturdy frame made of wood or metal. This implement is generally worked by a pair of animals.
- **0.4** It is pointed out that the requirements in regard to the materials included in this specification are only the minimum and the use of other materials having characteristics equivalent to or better than those specified in this standard is not precluded.
- **0.5** This standard is related to the manufacturing and trade practices prevailing in the country.
- 0.6 The Ministry of Food and Agriculture has desired that in order to make the standards more useful to those manufacturers who fabricate various agricultural implements and machinery on a small scale, it is necessary at this stage to include a typical design giving complete details for their information and guidance along with the standard the text of which shall be based on the policy decision taken by ISI on design standardization. Accordingly, a typical design as suggested by the Ministry giving complete details is included in the standard only for information and guidance. It is, however, pointed out that it is not in any way binding to those who do not wish to follow this design.
- 0.7 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated,

IS: 3369 - 1965

expressing the result of a test, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the requirements for puddler used in wet paddy fields and drawn generally by a pair of animals.

2. TERMINOLOGY

- 2.0 For the purpose of this standard, the following definitions shall apply.
- 2.1 Paddle The flat mild steel member in the shape of a blade which breaks up the clods and churns the soil.
- 2.2 Puddling Unit A unit consisting of four paddles connected to each other by a metal cross.

3. SIZE

3.1 The size of the puddler (see Fig. 1) shall be its maximum working width and this shall be determined by measuring the distance between the extreme points of the two outside puddling units. The size of the puddler shall be at least 725 mm (see Note).

NOTE — The size of the puddler may be as large as 2 m or even more. But, generally, the largest size of the puddler used in the country is of 2 m and this can be drawn conveniently by a pair of animals.

4. SHAPE AND DIMENSIONS

- **4.1 Shape** The shapes of the various parts of a typical puddler are shown in Fig. 1.
- **4.2 Dimensions** The dimensions of the various parts of the puddler (see Fig. 1), other than those specified in the text, are with reference to a particular type of the puddler and are for guidance only.

5. WEIGHT

5.1 The weight of the puddler including its beam shall be within a range of 30 to 40 kg.

6. DESCRIPTION

- 6.1 The puddler shall have the following main parts and their assembly is shown in Fig. 1 (see P 6):
 - a) Frame;

^{*}Rules for rounding off numerical values (revised).

- b) Puddling unit:
 - 1) Paddles,
 - 2) Metal cross;
- c) Axle;
- d) Bearings;
- e) Beam;
- f) Handle; and
- g) Handle supports.

7. MATERIALS

7.1 The requirements of the materials used for the various parts of the puddler shall be as given in Table 1.

TABLE I REQUIREMENTS OF MATERIALS FOR THE VARIOUS PARTS
OF THE PUDDLER, ANIMAL DRAWN

St No.	Name of Parts	MATERIAL	Applicable Standard	GRADE
(1)	(2)	(3)	(4)	(5)
i)	Frame	Wood or mild steel	IS: 399-1963*, IS: 808-1957† or IS: 1731-1961‡	
ii)	Paddle	Mild steel	IS: 226-1962§	
iii)	Metal cross	Mild steel or cast iron	IS : 226-1962 §, or IS : 210-1962	 15
iv)	Axle	Mild steel	IS: 226-1962§	
v)	Bearings	Cast iron or suitable well-seasoned wood impregnated with oil	IS: 210-1962 , or IS: 399-1963*	15 —
vi)	Beam	Wood	IS: 399-1963*	
víí)	Handle	Wood	IS:399-1963*	
viii)	Handle supports	Mild steel (angle section)	IS: 226-1962§	_

^{*}Classification of commercial timbers and their zonal distribution (revised).

||Specification for grey iron castings (revised).

[†]Specification for rolled steel beam, channel and angle sections.

[†]Dimensions for steel flats for structural and general engineering purposes.

[§]Specification for structural steel (Standard quality) (third revision).




Fig. 1

8. FRAME

8.1 The frame of the puddler shall consist of the front piece, the rear piece and the side pieces (see Fig. 1). The frame may be of mild steel flats, steel angle section or wood of suitable dimensions.

9. PUDDLING UNIT

- 9.1 The centre-to-centre distance between the two puddling units (see 2.2) shall be at least 250 mm (see Fig. 1) and shall not exceed 275 mm. The number of the puddling units in the puddler shall depend upon the size (see 3.1).
- 9.1.1 Paddles The paddles shall be fabricated from mild steel sheet having minimum thickness of 3.15 mm. Each paddle shall be made 225 mm long and 125 mm broad. The paddles shall be securely riveted to the metal cross (see 9.1.2).
- **9.1.2** Metal Cross The metal cross to hold four paddles shall be fabricated from mild steel flat of at least 5×55 mm size. It may also be of cast iron with suitable dimensions as a single unit (see Fig. 1). It shall have a suitable central opening to allow the passage of the axle (see 10.1) and shall be fixed in position by pinser studs.

10. AXLE

10.1 The mild steel axle shall be made of a bar of not less than 25 mm in diameter. The axle may also be of mild steel pipe having an internal diameter of 25 mm.

11. BEAM

11.1 One end of wooden beam shall be suitably fixed to the frame with the help of braces (see Fig. 1) and the other end to the yoke for hitching the animals.

12. HANDLE

12.1 The wooden handle shall be attached to the handle supports (see Fig. 1), the ends of which in turn shall be attached to the frame. The diameter and the length of the handle shall be not less than 50 mm and 600 mm respectively. The height of the top of the handle from the ground level shall be between 900 and 1 100 mm.

IS: 3369 - 1965

12.1.1 Handle Supports — The handle supports shall be fabricated from mild steel flats having minimum dimensions of 25×6.0 mm or angle section having minimum dimensions of $25 \times 25 \times 5.0$ mm.

13. BEARINGS

13.1 If the bearings are of cast iron they shall be so assembled that it shall be easy to lubricate and replace them when desired.

14. SAMPLING AND ACCEPTANCE

14.1 Unless otherwise agreed to between the purchaser and the supplier, the sampling plan and criteria for conformity given in Appendix A shall be followed.

15. WORKMANSHIP AND FINISH

15.1 The riveting or bolting shall be satisfactory in all respects. The exposed metallic parts shall be painted with rust-preventive anti-corrosive paint. The axles and bearings shall be coated with rust-proof grease prior to assembly. The timber parts of the puddler shall be painted before assembly.

16. MARKING

- 16.1 The puddler shall be marked with the following particulars:
 - a) Manufacturer's name and recognized trade-mark, if any;
 - b) Year of manufacture; and
 - c) Size of the puddler.
- **16.1.1** The marking shall be done on a metallic plate soundly riveted on a non-wearing part of the puddler.
 - 16.1.2 Each puddler may also be marked with the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act, and the Rules and Regulations made thereunder. Presence of this mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard, under a well-defined system of inspection, testing and quality control during production. This system, which is devised and supervised by ISI and operated by the producer, has the further safeguard that the products as actually marketed are continuously checked by ISI for conformity to the standard. Details of conditions, under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

APPENDIX A

(Clause 14.1)

SAMPLING OF PUDDLER, ANIMAL DRAWN

A-1. SCALE OF SAMPLING

- A-1.1 Lot In any consignment all the puddlers of the same type, shape and size and manufactured from the same materials under relatively similar conditions of manufacture shall be grouped together to constitute a lot.
- A-1.2 For ascertaining the conformity to this specification, the test shall be carried out separately for each lot.
- A-1.3 The number of puddlers to be sampled from a lot for ascertaining the conformity to the requirements of this specification shall be according to col 2 of Table 2.

TABLE 2 SCALE OF SAMPLING AND PERMISSIBLE NUMBER OF DEFECTIVES

Number of Puddlers in the Lot		FOR VISUAL AND DIMENSIONAL TESTS		For Trets Other than Visual and Dimensional		
			Number of Puddlers in the Sample	Permissible No. of Defec- tive Puddlers	Number of Puddlers in the Sample	Permissible No. of Defec- tive Puddlers
	(1)		(2)	(3)	(4)	(5)
υ	p to	100	5	0	2	0
	101 to	300	13	1	3	0
	301 ,,	500	32	3	5	0
	501 ,, 10	000	50	5	8	1
1	1 001 and a	bove	80	7	13	2

A-1.3.1 The puddlers shall be selected at random from the lot. To ensure the randomness of selection a random number table as agreed to between the purchaser and the supplier shall be used. In case such a table is not available, the following procedure shall be used:

Starting from any puddler, count them as 1, 2, 3,..........up to r and so on in one order where r is the integral part of N/n (N being the number of puddlers in the lot and n the number of puddlers to be selected in the sample). Every rth puddler thus counted shall be withdrawn to give the required number of puddlers in the sample.

IS: 3369 - 1965

A-2. NUMBER OF TESTS AND CRITERIA FOR CONFORMITY

A-2.1 Tests for Visual and Dimensional Characteristics — The puddlers selected at random according to A-1.3.1 shall be examined for the visual and dimensional characteristics. A puddler failing to satisfy any one or more of these requirements shall be regarded as defective. The lot shall be considered as conforming to the requirement for these characteristics, if the number of defective puddlers in the sample does not exceed the number given in col 3 of Table 2.

A-2.2 Tests Other Than Visual and Dimensional — If the lot conforms in A-2.1 to the requirements for visual and dimensional characteristics, a sub-sample of size given in col 4 of Table 2 shall be taken from the puddlers selected in A-1.3.1. Each of the puddlers in the sub-sample shall be tested for the requirements of characteristics other than visual and dimensional. A puddler not satisfying anyone or more of these requirements shall be regarded as defective. The lot shall be considered to conform to these requirements, if the number of defectives in the sub-sample does not exceed the number given in col 5 of Table 2.

(Continued from page 2)

Members

COL E. P. RAJU

SHRI C. S. SRIDHARAN
SHRI T. H. NIRMAL (Alternate)

SHRI J. C. VERMA

SHRI K. S. YADAV

SHRI P. J. ZACHARIAH

TEST ENGINEER (Alternate)

Representing

Development Commissioner, Small Scale Industries (Ministry of Industry & Supply)

Indian Council of Agricultural Research, New Delhi

Ministry of Community Development & Co-operation

Directorate of Extension (Ministry of Food & Agriculture)

Tractor Training and Testing Station, Budni

(Ministry of Food & Agriculture)

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI-110002

Telelphones: 331 01 31 331 13 75

Telegrams: Manaksanstha (Common to all Offices)

Regional Offices:	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002	331 01 31
,	331 13 75
*Eastern: 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA 70005	437 86 62
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160 022	60 38 43
Southern: C.I.T. Campus, IV Cross Road, MADRAS 600113	235 23 15
†Western : Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	832 92 95
Branch Offices:	Practice and the second
'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380001	30 13 48
‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road,, BANGALORE 550058	39 49 55
Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar, BHOPAL 462003	55 40 21
Plot No. 21 Satyanagar, BHUBANESHWAR 751007	40 36 27
Kalaikathir Building, 6/48 Avanashi Road, COIMBATORE 641037	21 01 41
Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001	8-28 88 01
Savitri Complex, 116 G.T. Road, GHAZIABAD 201001	8-71 19 96
53/5 Ward No. 29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003	54 11 37
5-8-56C L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001	20 10 83
R 14 Yudhister Marg, C Scheme, JAIPUR 302005	38 13 74
117/418 B Sarvodaya Nagar, KANPUR 208005	21 68 76
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001	23 89 23
Patliputra Industrial Estate, PATNA 800013	26 23 05
C/o Smt. Sunita Mirakhur,,	
66 D/C Annexe, Gandhi Nagar, JAMMU TAWI 180004	
T.C. No. 14/1421, University P.O., Palayam, THIRUVANANTHAPURAM 695034	6 21 17
Inspection Offices (With Sale Point):	
Pushpanjali, Ist floor, 205-A, West High Court Road, Shankar Nagar Square, NAGPUR 440010	525171
Institution of Engineers (India) Building 1332 Shivaji Nagar, PUNE 411005	32 36 35
* Sales Office is at 5 Chowringhee Approach, P.O. Princep Street, CALCUTTA 700072	27 99 65
†Sales Office is at Novelty Chambers, Grant Road, BOMBAY 400007 ‡Sales Office is at 'F' Block, Unity Building, Narasimharaja Square, BANGALORE 560002	309 65 28 22 39 71